

# TRUE MANUFACTURING CO., INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

| Project Name: |      | AIA#  |
|---------------|------|-------|
| Location:     |      |       |
| Item #:       | Qty: | SIS # |
| Model #:      |      |       |

Model:

TFP-64-24M-D-4~SPEC3

**Food Prep Table:** 

Drawered Food Prep Unit~Spec Package 3



# TFP-64-24M-D-4~SPEC3

- True's food prep units are designed with enduring quality that protects your long term investment.
- Energy saving, environmentally friendly (R513A), exclusive forced-air refrigeration system holds 33°F to 41°F (.5°C to 5°C).
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel
- Stainless steel, patented, foam insulated lid and hood keep pan temperatures colder, lock in freshness and minimize condensation. Removable for easy cleaning.
- Interior attractive, clear coated aluminum liner. Stainless steel floor with coved corners.
- ▶ 8" (204 mm) deep, ½" (13 mm) thick, full length removable cutting board included. Sanitary, high density white polyethylene provides tough preparation surface.
- Each drawer accommodates two (2) full size 12"L x 20"W x 6"D (305 mm x 508 mm x 153 mm) food pan (sold separately). Drawer will support varying size pan configurations with available pan divider bars (drawer pans sold separately).
- Heavy-duty stainless steel drawer slides and rollers.
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

# **ROUGH-IN DATA**

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

|                      |         | Cabinet Dimensions<br>(inches)<br>(mm) |     |      |     |          | NEMA | Cord<br>Length<br>(total ft.) | Crated<br>Weight<br>(lbs.) |      |
|----------------------|---------|--|-----|------|-----|----------|------|-------------------------------|----------------------------|------|
| Model                | Drawers | W                                      | D†  | H*   | HP  | Voltage  | Amps | _                             | (total m)                  | (kg) |
| TFP-64-24M-D-4~SPEC3 | 4       | 641/8                                  | 31½ | 45¾  | 1/3 | 115/60/1 | 4.8  | 5-15P                         | 7                          | TBD  |
|                      |         | 1629                                   | 801 | 1162 | N/A |          | N/A  |                               | 2.13                       | TBD  |

<sup>†</sup> Depth does not include 2" (51 mm) for cutting board.

<sup>\*</sup> Height does not include ¾" (19 mm) for castors.

| MADE WITH INNOVATION IN THE USA |                   |  | AVAILABLE AT: |  |  |
|---|-------------------|--|---------------|--|--|
| 2/22  | Printed in U.S.A. |  |               |  |  |

TFP-64-24M-D-4~SPEC3

# **Food Prep Table:**

Drawered Food Prep Unit~Spec Package 3



# STANDARD FEATURES

#### DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.

#### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) R513A refrigerant.
- Energy saving, factory balanced refrigeration system with guided airflow to provide uniform temperature in food pans and cabinet interior.
- Exclusive forced-air design holds 33°F to 41°F (.5°C to 5°C) product temperature in food pans and cabinet interior. Complies with and listed under ANSI/NSF-7.
- High efficiency evaporator fan motor and larger fan blades give True Food Prep units a more efficient, low velocity, high volume airflow design.
- Easy access to all condensing unit components from back of cabinet.

### **CABINET CONSTRUCTION**

- Exterior stainless steel front, top, sides, and back.
- Interior Stainless steel liner. Stainless steel floor with coved corners.

- Insulation entire cabinet structure and drawer facings are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- 2½" (64 mm) diameter castors locks provided on front set.
- Solid State Electronic Control, accessible on back of the unit.

#### **DRAWERS**

- Stainless steel exterior drawer facings and liners. Stainless steel drawer frames.
- Drawer locks standard.
- Each drawer fitted with Lifetime guaranteed heavy duty all metal working spec handle.
- Magnetic drawer gaskets of one piece construction, removable without tools for ease of cleaning.
- Heavy-duty stainless steel drawer slides and rollers. Removable without tools for easy cleaning.
- Each drawer accommodates two (2) full size 12"L x 20"W x 6"D (305 mm x 508 mm x 153 mm) food pan (sold separately). Drawer will support varying size pan configurations with available pan divider bars (drawer pans sold separately).

#### **MODEL FEATURES**

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- 8" (204 mm) deep, full length removable cutting board. Sanitary, high-density white polyethylene provides tough preparation surface.

- Stainless steel, patented, foam insulated lid and hood keep pan temperatures colder, lock in freshness and minimize condensation. Removable for easy cleaning.
- Comes standard with 24 (%size) 6 %"L x 6 ¼ "W x 4"D (175 mm x 159 mm x 102 mm) clear polycarbonate food pans in countertop prep area.
- Countertop pan opening designed to fit varying size pan configurations with available pan divider bars. Varying size pans supplied by others.
- NSF/ANSI Standard 7 compliant for open food product.

#### **ELECTRICAL**

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



### **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply.

- ☐ Pan dividers
- ☐ Sinale overshelf
- ☐ Double overshelf
- ☐ Cutting boards provided by others. Requires "L" brackets. Field installed brackets provided by True (contact factory).

PLAN VIEW

# Drawing Not Yet Available

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

| ſ | KCL | Model                | Elevation | Right | Plan | 3D | Back |
|---|-----|----------------------|-----------|-------|------|----|------|
| l |     | TFP-64-24M-D-4~SPEC3 |           |       |      |    |      |